



HYDRAULIC HAMMERS

MODEL NUMBER	OPERATING WEIGHT LB (KG)	ENERGY CLASS FT-LB	TOOL DIAMETER IN (MM)	OIL FLOW GPM (LPM)	OPERATING PRESSURE PSI (BAR)	IMPACT RATE BPM	CARRIER WEIGHT LBS (TON)
AB 307	664 (301)	550	2.75 (70)	9-19 (35-70)	1600-2400 (110-165)	380-1000	6600-14300 (3.0-6.5)
AB 408	950 (431)	800	2.95 (75)	10-20 (40-80)	1740-2390 (120-165)	380-900	9900-17600 (4.5-8.0)
AB 509	1105 (495)	1000	3.15 (80)	12-24 (45-90)	2030-2470 (140-170)	400-1100	9900-20000 (4.5-9.0)
AB 610	1343 (609)	1400	3.54 (90)	13-26 (50-100)	2030-2470 (140-170)	350-1000	13200-22000 (6.0-10.0)
AB 1015	2324 (1054)	2500	4.13 (105)	21-37 (80-140)	2030-2610 (140-180)	350-900	22000-33000 (10-15)
AB 1218	2860 (1297)	3500	4.52 (115)	26-40 (100-150)	2330-2755 (140-180)	320-700	26400-39600 (12-18)
AB 1824	3940 (1787)	4500	5.31 (135)	32-45 (120-170)	2320-2760 (160-190)	320-800	39600-52800 (18-24)
AB 2026	4332 (1965)	5500	5.31 (135)	37-50 (140-190)	2320-2760 (160-190)	340-800	44000-57200 (20-26)
AB 2230	4670 (2118)	6500	5.70 (145)	40-55 (150-210)	2320-2760 (160-190)	300-720	48000-66000 (22-30)
AB 2842	6984 (3168)	8000	6.10 (155)	53-69 (220-260)	2320-2760 (160-190)	230-600	61600-92400 (28-42)
AB 3450	7961 (3611)	10000	6.50 (165)	58-74 (220-280)	2320-2760 (160-190)	230-600	74800-110000 (34-50)
AB 4060	9222 (4183)	12000	6.90 (175)	63-84 (240-320)	2320-2760 (160-190)	230-550	88000-132000 (40-60)
AB 4580	10344 (4692)	14000	7.08 (180)	69-95 (270-370)	2320-2760 (160-190)	270-550	99000-176000 (45-80)

- Silenced - Enclosed Bracket
- Stroke Adjuster (variable speed control)
- Anti Blank Fire
- On Board Shock Damping
- Auto Lube Systems Available
- Two Moving Parts
- Oversized Accumulator (protects hydraulic circuit)
- Oversized Tie Rods (longer lasting)
- 550 to 14,000 ft-lb models available
- Fits 3 to 80 ton carriers

REBEL ATTACHMENTS

BY ALLIED PEDESTAL BOOM SYSTEMS

(419) 663-1048 | Norwalk, OH | alliedpbs.com