

MELLOTT®

TECHNICAL DATA - MC106P



VIBRATING GRIZZLY FEEDER

- 42'x17' Vibrating Feeder
- 40 HP, 1200 RPM, TEFC Electric Motor
- 12' Pan w/ Replaceable ½" AR Liners
- 5' Grizzly Section w/ Adjustable Bars

JAW CRUSHER

- Metso C106 Jaw w/ Integral Motor Mount
- Feed Opening 42"(W)x34"(D)
- 150 HP, 1200 RPM TEFC Crusher Duty Motor
- Closed Side Setting 2 ¾"-8"
- Composite Guards, Crusher Side Feed Chute

CHASSIS

- Heavy Duty Fabricated Frame Complete with Cribbing Supports
- Triple Axle Suspension w/ 12 11R24.5 Tires
- Road Ready (Airbrakes, Mud Flaps)

UNDER CRUSHER CONVEYOR

- 42" BW x 30' Long Conveyor
- 15 HP Motorized Head Pulley
- Channel Frame Construction
- CEMA C5 Idlers
- 4' Long Impact Bed at Loading Zone
- Belt Scraper

AVAILABLE OPTIONS

- Pre-Wired Electrical Starter Panel
- Hydraulic Lifting Legs
- Breaker w/Support Structure
- Control House

