


TECHNICAL DATA - MC1215B



CHASSIS

- Wide Flange Fabricated Frame Complete with Cribbing Supports
- Manual 4-Point Leveling System
- Tandem Axle Suspension with 8 11T24.5 Tires
- Road Ready (Air Brakes, Mud Flaps)

FEEDER

- 36" x 72" Pan with Controller
- Syntron MF200 Electro Mechanical Vibrating Feeder
- 1/4" T1A Liners
- 4 HP Below Deck Drive

RECEIVING HOPPER

- 12' X 15' Top Opening with Winged Hopper Extensions
- 36 Cubic Yard Water Level Capacity
- Hopper Constructed from 1/2 " Mild Steel Plate w/ 3/8 " Mild Steel Extensions

RECEIVING HOPPER


- Max Feed Bin Size 6"
- Maximum Plant Capacity Up to 600 TPH
- Maximum Bin Capacity 36 Cubic Yards

CONVEYOR - 42" X 50' LONG


- 20 HP Drive Consisting of 1 20 HP, 1800 RPM, TEFC Electric Motor, Dodge TAII TA4207H25 Class II, Rod Assembly, bushing, backstop, motor mount, Drive Guard
- Channel Frame Construction with Hinge for Travel
- CEMA 5 Idlers
- 2 Melott Company Standard Return Roll Guards at Tail-**End of Conveyor**
- 3-Ply, 450 PIW, $\frac{1}{4}$ " x 1/16 , Impact Abrasion Resistant Cover, Belting w/ Flexco Mechanical Belt Slice



TECHNICAL DATA - MC1215B



Travel Position



Operational Position

PHYSICAL/OPERATING CHARACTERISTICS

•	Overall Length51'-2 ½"	• Feed Height16'-10 % "
	Travel Height13'-8 % "	Maximum Discharge Clearance16'-8 ½ "
	Overall Width12'- 1⁄4 "	Maximum Discharge Height18'-2 7/16"

Total Shipping Unit Weight38,000 lbs

Specifications are subject to change without notice

MAIN OFFICE 100 Mellott Drive Warfordsburg, PA 17267 Marion, NC 28752

SOUTHERN SERVICE CENTER 169 Machine Shop Rd.

KASTROCK 2520 McJunkin Rd.

55 Boulderbrook Circle Lakeland, FL 33803 Lawrenceville, GA 30045 Nashville, TN 37211

SOUTHERN MACHINERY 3735 Vulcan Drive

VISIT US AT MELLOTTCOMPANY.COM CUSTOMER SERVICE HOTLINE: 800.634.5634

EMAIL: SALES@MELLOTTS.COM